

# Rittal – The System.

Faster – better – everywhere.

## ► Support strip for VX, TS, SE, CM, TP, AX – TS 4697.000

Date : Jan 28, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Support strip for VX, TS, SE, CM, TP, AX – TS 4697.000

created: 28.01.2020 build on www.rittal.com/uk-en



## Product description

<b>Description:</b>	For simple attachment of cable ducts, cable conduit holders, contact hazard protection cover plates, equipment installed on the door, cable clamping and attachment.
<b>Material:</b>	Sheet steel
<b>Surface finish:</b>	Zinc-plated
<b>Technical specifications:</b>	4.5 mm diameter hole on a 25 mm DIN pitch pattern.
<b>Supply includes:</b>	Assembly parts

## Product features

<b>To fit:</b>	Enclosure type: VX Enclosure type: TS Enclosure type: SE Width/depth: 800 mm
<b>Dimensions:</b>	Length: 740 mm
<b>Installation options:</b>	On the inner and outer mounting level, on the enclosure section For cable routing from the mounting plate to the door In the AX enclosure door with cam lock On the perforated door strip in AX stainless steel
<b>Packs of:</b>	20 pc(s).
<b>Weight/pack:</b>	7.64 kg

<b>Copper weight (kg per piece):</b>	0
<b>EAN:</b>	4028177108172
<b>Customs tariff number:</b>	73269098
<b>ETIM 7.0:</b>	EC002620
<b>ETIM 6.0:</b>	EC002620
<b>eCl@ss 8.0/8.1:</b>	27189261
<b>eCl@ss 6.0/6.1:</b>	27189261
<b>Product description:</b>	TS Support strip, for TS, SE, CM, TP, for the outer mounting level: for W/D: 800 mm, L: 740 mm
<b>Approvals</b>	
<b>Certificates:</b>	EAC