

# Rittal – The System.

Faster – better – everywhere.

► **Network/server enclosure TS IT with glazed door, pre-configured, with 482.6 mm (19") mounting frame – DK 5527.151**

Date : Mar 21, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Network/server enclosure TS IT with glazed door, pre-configured, with 482.6 mm (19") mounting frame – DK 5527.151

created: 21.03.2018 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

<b>Material:</b>	Sheet steel Aluminium Base/plinth: Fibreglass-reinforced plastic Glazed door: Single-pane safety glass, 3 mm
<b>Surface finish:</b>	Enclosure frame: Dipcoat-primed Interior installation: Dipcoat-primed Doors, roof and side panels: Dipcoat-primed and powder-coated
<b>Colour:</b>	Enclosure frame and panels: RAL 7035 Interior installation, base/plinth: RAL 9005
<b>Supply includes:</b>	Enclosure frame TS 8 with doors, roof plate, base/plinth and side panels Glazed aluminium door at the front, 180° hinges Lock front and rear: Comfort handle for semi-cylinders and security lock 3524 E Two 482.6 mm (19") mounting frames, front and rear, depth-variable Spacers to raise the fan cover plate, for passive cooling (supplied loose) Connection accessories for potential equalisation incl. central earthing point, pre-configured 50 multi-tooth screws M5, cage nuts M5, conductive (supplied loose) Base mount Base module mounted at front as infill panel Flex-Block base/plinth 100 mm, vented, fitted base/plinth corner pieces, base/plinth trim panels (supplied loose) Side panels, one-piece, lockable 4 levelling feet, M12, including base/plinth adaptor sleeve (supplied loose) 4 cable clamp rails (T-head) for outer mounting level, to fit enclosure depth (supplied loose) 10 cable shunting rings (metal version), 125 x 65 mm (supplied loose) IPPC pallet 1 Roof plate, multi-piece, removable, for horizontal cable entry at the rear and covered cut-out for fan mounting plate 1 Sheet steel door at the rear, vertically divided, 180° hinges

<b>Note:</b>	Depending on how and where it is sited, the door opening angle may vary for selected applications
<b>Basic material:</b>	Sheet steel
<b>Product features</b>	
<b>Dimensions:</b>	Width: 600 mm Height: 1800 mm Height (enclosure with plinth): 1900 mm Depth: 600 mm
<b>Installation height for components:</b>	38 U
<b>Distance between levels as delivered:</b>	345 mm
<b>482.6 mm (19") version:</b>	Mounting frame, 482.6 mm (19")
<b>Load capacity:</b>	10000 N
<b>Packs of:</b>	1 pc(s).
<b>Weight/pack:</b>	122 kg
<b>EAN:</b>	4028177706415
<b>Customs tariff number:</b>	94032080
<b>ETIM 6.0:</b>	EC002499
<b>ETIM 5.0:</b>	EC002499
<b>eCl@ss 8.0/8.1:</b>	27180207
<b>eCl@ss 7.0/7.1:</b>	27180207
<b>eCl@ss 6.0/6.1:</b>	27180207
<b>eCl@ss 5.1/5.1.4:</b>	27180201
<b>Product description (long):</b>	DK Network/server enclosure TS IT, with 19" mounting frame, WHD: 600x1800+100x600 mm, 38 U, pre-configured, Glazed aluminium door at the front, Sheet steel door at the rear, vertically divided,
<b>Approvals</b>	
<b>Approvals:</b>	UL + C-UL

---

**Declarations:**

Declaration of conformity

---