

Data sheet

SE 5834.500



Main data:

Model No.:	SE 5834.500
Designation:	SE system enclosure based on TS 8, WHD 800x2000x600 mm, single-door,
Variant:	n/a
Packs of:	1 ST
W x H x D:	800 mm x 2.000 mm x 600 mm
Mounting surface:	n/a
Volume:	1061,48 dm ³
Net weight:	142,00 kg
EAN:	4028177666474
Customs number:	94032080
Protection categories:	n/a

Approbationen:

CE	1 602 201
CUL	E 76083
HE	1 600 112
UL	E 76083

Article features:

Material	Sheet steel <(>,, <)>-,,Enclosure 1.5 mm <(>,, <)>- Door 2.0 mm <(>,, <)>- Rear panel 1.5 mm Sheet steel, zinc-plated
-----------------	---

Data sheet

SE 5834.500



<(>,, <)>- Gland plates 1.5 mm

<(>,, <)>- Mounting plate 3.0 mm

Colour

Enclosure, door, rear panel: RAL 7035, dipcoat primed, externally powder-coated, textured paint

Technical specifications

Protection category: IP 55 to EN 60 52, complies with NEMA 12

Supply includes

<(>,, <)>- Enclosure with 1 door, door hinged on the right (can be

changed to the left)

<(>,, <)>- Mounting plate

<(>,, <)>- Gland plates, divided

<(>,, <)>- Rear panel screw-fastened from the inside

Product notes

The system enclosure SE 8 is based on the TS 8 platform. Full compatibility with the TS 8 system accessories for interior

installation,

e.g. TS 8 and PS punched sections with mounting flanges, TS 8 and PS

punched sections without mounting flanges, TS 8 and PS punched rails (see Catalogue 32, page 988 ff.). Merely in the roof frame TS 8 punched sections with mounting flanges can

exclusively be used in the enclosure depth.

The TS base/plinth and the Flex-Block base/plinth system can be used.

Texts for tenders:

FRIEDHELM L O H GROUP

Single-door sheet steel system enclosure

Enclosure for stand-alone siting in self-supporting page 2

integrated construction, consisting of a basic frame.

Data sheet

SE 5834.500



of one-piece construction including side panels and roof. Enclosure section with system punchings on a 25 mm DIN pitch pattern. Vertical sections as well as front and rear roof frame section with two mounting levels for space-saving system installation. Screw-fastened rear panel, welded base assembly consisting of base frame and multi-divided, sliding gland plates, r/h door hinge

Door:

With horizontally double foamed-in seal, with removable rectangular frame with holes on a 25 mm DIN pitch pattern, locking bar with 4-point latching, double-bit insert to DIN 43668, r/h door hinge may be swapped to opposite side, with captive hinge pins, door opening angle 130° to VDI, may be retrofitted to 180°, automatic potential equalisation to the enclosure frame.

Gland plates:

3-part, removable and replaceable, fitted, automatic potential equalisation to the enclosure frame.

Rear panel:

With foamed-in seal, screw-fastened, automatic potential equalisation to the enclosure frame.

Mounting plate:

C-folds at the sides, depth-adjustable on a 25 mm pitch pattern via integrated plastic slide pieces. Punched rail in the base for easy sliding of mounting plate may be removed after positioning the mounting

Data sheet

SE 5834.500



plate and located on the vertical sections, e.g. for cable routing.

Material (material thickness):

Sheet steel for enclosure (1.5 mm), rear panel (1.5 mm), door (2.0 mm), gland plates (1.5 mm) and mounting plate (3.0 mm)

Surface finish:

3 layers of surface protection: Nanoceramic coating, electrophoretic dipcoat-priming, powder-coating in textured RAL 7035 on the outside.

Mounting plate and gland plates: Zinc-plated

Protection category:

IP 55 to EN 60 529, complies with NEMA 12.

Dimensions:

Width x height x depth: 800x2000x600 mm,

mounting plate (width x height): 699x1896 mm

Make/model:

Rittal SE 5834.500 (or equivalent)