


Rittal – The System.

Faster – better – everywhere.



AX 6315.350

Compact enclosure AX

State: 16/01/2023 (Source: rittal.com/com-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AX 6315.350 - Compact enclosure AX Operating housings AX with handle strips

Operating housing with handle strips based on sheet steel AX, with support arm cut-out Ø 130 mm to fit support arm system CP 60/120/180, service access from the front, aluminium front panel easily removable for machining, protection category IP55.

Features

Model No.	AX 6315.350
Product description	The operating housing with handle strips, based on AX, sheet steel, with a Ø 130 mm support arm cut-out to fit support arm system CP 60/120/180, service access from either the front or the rear, aluminium front panel easily removable for machining, protection category IP 55.
Material	Enclosure: Sheet steel Door: Sheet steel, all-round foamed-in PU seal Front panel: Aluminium Cover caps: Plastic
Surface finish	Enclosure and door: Dipcoat primed, powder-coated on the outside, textured paint Handle strip: Natural anodised Front panel: Natural anodised
Colour	Enclosure and door: RAL 7035 Handle strip: Natural anodised Front panel: Natural anodised Cover caps: similar to RAL 7024
Supply includes	Enclosure with cut-out and reinforcement for support arm connection Ø 130 mm Front with maximum cut-out, covered with easily machinable 3 mm aluminium front panel Side handle strips with cover caps Integral interior installation bracket with system punchings Cam lock with 3 mm double-bit insert

Features

Dimensions	Width: 380 mm Height: 380 mm Depth: 210 mm
Standard	NEMA 1, 12
Type rating to UL 50E	Type 1, 12
Version with service access	from the front
IK Code	IK08
Note	The support arm connection and door hinge may be swapped over by rotating the enclosure Optional: Support arm connection Ø 130 mm, preformed off-centre in the reinforcement plate, easily drilled out Lock systems for servicing access from the rear: Lock insert may be exchanged for mini comfort handle AX, 27 mm lock inserts, type A Lock systems for servicing access from the front: Lock insert may be exchanged for 27 mm lock inserts, type A
Basic material	Sheet steel
Note on Model No.	Matching mounting panel 5051.371 with dispatch bag 5051.300
Packs of	1 pc(s).
Weight/pack	9.8 kg
Copper weight (kg per piece)	0
Customs tariff number	94032080
EAN	4028177923157
ETIM 7.0	EC002504
ECLASS 8.0	27180505

Approvals

Approvals	GOST UL + C-UL (listed)
-----------	----------------------------

Approvals

Explanations

Declaration of conformity

Declaration of conformity UK