Rittal - The System.

Faster - better - worldwide.

Socket strip – DK 7000.630

Date : Sep 3, 2013



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES



Product description

Description:

8-way socket strip for earthing-pin plug/version D. The strip is made of plastic and may be mounted vertically on the TE frame or in the rear 482.6 mm (19") section. In the 482.6 mm (19") section, more than 2 U of space is required. The sockets are arranged at an angle of 45?? so that angular connectors are also easily used. The connection cable is contacted in a terminal slot in the strip. The terminal slot has a separate cover and external terminals for separate earthing.

Material:

Plastic

Supply includes:

Connection cable Socket strip Assembly screws 2 serrated washers

Captive nuts M6, conductive

Nuts

Packs of:

1 pc(s).

EAN:

4028177438569

Customs tariff number:

85369085

Product features

Design:

Without switch

Installation options:

TE 7000, rear 482.6 mm (19") section (> 2 U) TE 7000, vertically mounted on the frame

Rated voltage:

230 V AC

© Rittal 2013

Rated current (max.):	16 A
Equipment (electrical):	Number of sockets: 8 Jack/socket (type): D, earthing-pin (type F, CEE 7/4) Length of connection cable: 2 m
Connection cable (type):	H05VV-F3G1.5 with wire end ferrules
Approvals	
Certificates	Sorry, there is currently no information available
Declarations	☑ Declaration of conformity (EN, DE)
Approvals	Sorry, there is currently no information available
Downloads / CAD	
Documentation	Sorry, there is currently no information available
Characteristic curves	Sorry, there is currently no information available
Videos	Sorry, there is currently no information available
Data sheets	Sorry, there is currently no information available
CAD-Drawing	Sorry, there is currently no information available

© Rittal 2013 2

Rittal – The System.

Faster - better - worldwide.

- Enclosures
- Power distribution
- Climate control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG Postbox 1662 · D-35726 Herborn

Phone +49(0)2772 505-0 · Fax +49(0)2772 505-2319

E-Mail: info@rittal.com · www.rittal.com

