

# Data sheet

## DK 7240.110



### Main data:

|                               |   |
|-------------------------------|---|
| <b>Model No.:</b>             | DK 7240.110   |
| <b>Designation:</b>           | Socket strip 3 sockets, 250V/16A,<br>without switch |
| <b>Variant:</b>               | n/a   |
| <b>Packs of:</b>              | 1 ST  |
| <b>W x H x D:</b>             | 263 mm x 44 mm x 44 mm                              |
| <b>Mounting surface:</b>      | n/a   |
| <b>Volume:</b>                | 2,52 dm <sup>3</sup>                                |
| <b>Net weight:</b>            | 0,50 kg   |
| <b>EAN:</b>                   | 4028177255272                                       |
| <b>Customs number:</b>        | 85369085  |
| <b>Protection categories:</b> | n/a   |

### Approbationen:

|            |           |
|------------|-----------|
| <b>CE</b>  | 5 371 712 |
| <b>VDE</b> | 40026888  |

### Article features:

### Texts for tenders:

Socket strip with 3 sockets, switchless, 250V/16A  
2 angle brackets are needed to fix the socket strip in the network enclosure. The socket strip has 3 earthing contact sockets fitted in it. It is an aluminium section, natural anodised enclosure. The socket cups are made from polycarbonate.

### Technical specifications:

FRIEDHELM LOH GROUP

**Rated voltage: 250V AC**

# Data sheet

## DK 7240.110



**Rated current: 16A**

**Connection cable: 2 m, grey, without connector,  
H05VV-F3G1.5**

**Dimensions: 262.6 x 44.2 x 44 mm, DIN 49440**