

Rittal – The System.

Faster – better – everywhere.

▶ Socket strips in an aluminium duct – DK 7240.210

Date : Apr 15, 2015

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Socket strips in an aluminium duct – DK 7240.210

created : 15.04.2015 on www.rittal.com/com-en



Product description

Description:	The socket strips in the aluminium duct are available in various country-specific variants with different functional elements. Special attention has been devoted to practical, universal fastening: Variable attachment facilities have been created with an angle bracket which may be inserted in four positions. Hence, for example, the 482 mm long socket strip may optionally be mounted on 482.6 mm (19") mounting angles, the 482.6 mm (19") mounting frame, on the enclosure frame, or in the rear section of the wall-mounted distributor. Without additional mounting accessories, the socket strip may be inserted into all sections with a 25 mm hole pattern. This makes selection much easier, as well as providing additional flexibility and saving on warehousing. Provision has also been made for cable routing of the infeed, and when mounting in the 482.6 mm (19") section there is adequate space to route the infeed between the socket strip and the profile rail without kinks. The arrangement of the IEC 320 sockets at a 45° angle allows unrestricted use of angular connectors.
Material:	Aluminium section, natural anodised Socket inserts: Polycarbonate
Standards:	DIN 49 440-1
Supply includes:	Socket strip Two mounting brackets Assembly parts
Note:	Depending on the application, we recommend use of a charging current reserve to prevent incorrect activation due to starting-current spikes Variable attachment distance within a range of 25 mm, the distance given is hole centre – hole centre of mounting bracket
Packs of:	1 pc(s).
EAN:	4028177221161
Customs tariff	85369085

number:

eCl@ss 5.1: 27143401

eCl@ss 7.0: 27142604

Product features

Design: Without switch

Dimensions: Height: 44 mm
Depth: 44 mm

Installation options: Components with a 25 mm pitch pattern
Enclosure frame
IT wall-mounted distributor, at the rear, horizontal (adequate width provided)
482.6 mm (19") level

Length: 482.6 mm

Mounting dimensions: 452.5 mm
Tolerance: ± 25 mm

Rated voltage: 250 V AC

Rated current (max.): 16 A

Equipment (electrical): Number of sockets: 7
Jack/socket (type): D, earthing-pin (type F, CEE7/3)
Length of connection cable: 2 m

Connection cable (type): H05VV-F3G1.5

Weight/PU: 0.88 kg

Approvals

Approvals:  [VDE \(DE\)](#)

Declarations:  [Declaration of conformity \(DE\)](#)

Downloads

Data sheets:  [Technical details](#)
EN