

# Rittal – The System.

Faster – better – everywhere.

## ▶ **Socket strips in an aluminium duct – DK 7240.330**

Date : Apr 13, 2015

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Socket strips in an aluminium duct – DK 7240.330

created : 13.04.2015 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description



<b>Description:</b>	The socket strips in the aluminium duct are available in various country-specific variants with different functional elements. Special attention has been devoted to practical, universal fastening: Variable attachment facilities have been created with an angle bracket which may be inserted in four positions. Hence, for example, the 482 mm long socket strip may optionally be mounted on 482.6 mm (19") mounting angles, the 482.6 mm (19") mounting frame, on the enclosure frame, or in the rear section of the wall-mounted distributor. Without additional mounting accessories, the socket strip may be inserted into all sections with a 25 mm hole pattern. This makes selection much easier, as well as providing additional flexibility and saving on warehousing. Provision has also been made for cable routing of the infeed, and when mounting in the 482.6 mm (19") section there is adequate space to route the infeed between the socket strip and the profile rail without kinks. The arrangement of the IEC 320 sockets at a 45° angle allows unrestricted use of angular connectors.
<b>Material:</b>	Aluminium section, natural anodised Socket inserts: Polycarbonate
<b>Standards:</b>	DIN 49 440-1 Overvoltage protection for low voltage: DIN EN 61 643-11 (VDE 0675 Part 6-11)
<b>Supply includes:</b>	Socket strip Two mounting brackets Assembly parts
<b>Note:</b>	Depending on the application, we recommend use of a charging current reserve to prevent incorrect activation due to starting-current spikes Variable attachment distance within a range of 25 mm, the distance given is hole centre – hole centre of mounting bracket
<b>Packs of:</b>	1 pc(s).
<b>EAN:</b>	4028177221246

<b>Customs tariff number:</b>	85369085
<b>eCl@ss 5.1:</b>	27143401
<b>eCl@ss 7.0:</b>	27142604

## Product features

<b>Design:</b>	With overvoltage protection and interference suppression filter
<b>Dimensions:</b>	Height: 44 mm Depth: 44 mm
<b>Installation options:</b>	Components with a 25 mm pitch pattern Enclosure frame
<b>Length:</b>	658.6 mm
<b>Mounting dimensions:</b>	628.5 mm Tolerance: ± 25 mm
<b>Rated voltage:</b>	250 V AC
<b>Rated current (max.):</b>	16 A
<b>Equipment (electrical):</b>	Number of sockets: 9 Jack/socket (type): D, earthing-pin (type F, CEE7/3) Length of connection cable: 2 m
<b>Connection cable (type):</b>	H05VV-F3G1.5
<b>Weight/PU:</b>	1.2 kg

## Approvals

<b>Approvals:</b>	 <a href="#">VDE (DE)</a>
<b>Declarations:</b>	 <a href="#">Declaration of conformity (DE)</a>

## Downloads

<b>Data sheets:</b>	 <a href="#">Technical details</a> EN
---------------------	---