

# Data sheet

## DK 7643.000



### Main data:

<b>Model No.:</b>	DK 7643.000
<b>Designation:</b>	Wall-mounted enclosure (AE 1360), ,
<b>Variant:</b>	n/a
<b>Packs of:</b>	1 ST
<b>W x H x D:</b>	600 mm x 600 mm x 350 mm
<b>Mounting surface:</b>	n/a
<b>Volume:</b>	126,00 dm <sup>3</sup>
<b>Net weight:</b>	24,40 kg
<b>EAN:</b>	4028177147034
<b>Customs number:</b>	94032080
<b>Protection categories:</b>	IP 55

### Approbationen:

<b>BV</b>	04880_E1_BV
<b>GL</b>	69 280 - 90 HH
<b>LR</b>	04 / 20022
<b>TÜV</b>	B 12 03 12010 004
<b>TÜV</b>	B 12 03 12010 004 engl
<b>VDE</b>	6312 ÜG

### Article features:

### Texts for tenders:

Wall-mounted distributor enclosure with 482.6 mm (19") accommodation level, 13 U  
13 U wall-mounted distributor made from 1.5 mm sheet steel, gland plate with two cable entry brush strips

# Data sheet

## DK 7643.000



fitted in enclosure base, 2 mm sheet steel door with two cam locks and double-bit inserts, can be changed for a T-handle with security lock.

Doorstop interchangeable between left and right.

Two C rails are fitted on the left and right in the enclosure depth that enable linearly adjustable 482.6 mm (19") mounting angles to be mounted on each of them.

The cables can be fed in through the cutouts alongside the mounting angles. Incoming and outgoing cables are fed through the gland plate with the two brush strips into the enclosure base and are clamped to one of the C rails mounted in the width of the enclosure. A mounting plate with mounting holes for fitting a socket strip or a potential equalisation rail is installed above the C rail.

The gland plate with the two brush strips can be changed for plastic gland plate with PG gland knockouts

**Spray finish: RAL 7035, electrophoretic dipcoat,**  
textured on the outside

**Dimensions: W: 600 mm H: 600 mm D: 350 mm**