

# Rittal – The System.

Faster – better – everywhere.

## ► Mounting angles, 482.6 mm (19") for TS – DK 7827.201

Date : Apr 13, 2015

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Mounting angles, 482.6 mm (19") for TS – DK 7827.201

created : 13.04.2015 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

**Benefits:** Integral U markings in the front facilitate systematic assembly within the 482.6 mm (19") attachment level.  
L-shaped mounting angles accommodate the installation kits of server systems on Suitable for 482.6 mm (19") partial installation

**Material:** Sheet steel, 2 mm

**Technical specifications:** Integral 482.6 mm (19") punchings (EIA standard)  
Side round and square punchings  
Clear chromated for conductive connection of the 482.6 mm (19") installed equipment.

**Supply includes:** Assembly parts

**Packs of:** 2 pc(s).

**EAN:** 4028177234949

**Customs tariff number:** 73269098

**eCl@ss 5.1:** 27182504

**eCl@ss 7.0:** 27189261

## Product features

**Design:** L-shaped mounting angle

**To fit:** Enclosure type: TS

Height: = 2000 mm

---

**Units:** 42 U

---

**Weight/PU:** 4.84 kg

---

## Downloads

---

**Data sheets:**  [Technical details](#)  
EN

---

**CAD drawings:** Request

---