

Data sheet



Main data:

Model No.:	
Designation:	Top enclosure system, painted RAL 7035, with mounting plate, double-door mit Montageplatte, lackiert
Variant:	
Packs of:	1 ST
W x H x D:	1.000 mm x 2.000 mm x 500 mm
Mounting surface:	n/a
Volume:	1144,00 dm ³
Net weight:	149,25 kg
EAN:	4028177250826
Customs number:	85381000
Protection categories:	IP 55, NEMA 12

[You can find the product in Catalogue 32, page 144](#)

Approbationen:

BV	09639 / BO BV
CE	1 248 310
CE	1 333 701
CSA	LR 59132
DNV	E-8522
GL	15 644 - 00 HH
LR	07/20038
MRS	10.04048.250
TÜV	B 10 07 12010 008
TÜV-MARK	Z2 10 07 12010 009
UL	E 76083
VDE	6312 ÜG

Data sheet



Article features:

Material

Sheet steel
Enclosure frame, roof, rear panel and gland plates: 1.5 mm
Door: 2.0 mm
Mounting plate: 3.0 mm
Surface finish
Enclosure frame:
Door, roof and rear panel
Dipcoat-primed, powder-coated in textured RAL 7035 on the outside

Mounting plate and gland plates: Zinc-plated
Supply includes
Enclosure frame with doors, mounting plate, gland plates, rear panel and

roof plate
Technical specifications
Dimensions:
Width: 1000 mm
Height: 2000 mm
Depth: 500 mm
Door: 2
Weight: 157.1 kg

Texts for tenders:

Enclosure (baying system) double-door

Enclosure:

Symmetrical frame construction of rolled hollow sections with holes on a 25 mm DIN pitch pattern. All sections have chamfered edges. The horizontal sections have an additional protection lip above the seal.

Data sheet



The vertical sections have two mounting levels for space-saving interior installation.

Bayable on all sides.

Four eyebolts, three-piece gland plate can be removed and interchanged, fitted.

Doors:

2 mm sheet steel, with foamed-in seal, with removable tubular door frame with holes on a 25 mm DIN pitch pattern, lockable door on the r/h side with 4-point latch locking rod, double-bit insert to DIN 43668.

Adjacent door additionally locked at top and bottom with swing lever. Hinges with captive hinge pins, door opening angle 130° to VDI, can be retrofitted to 180°, floor clearance 25 mm.

Rear panel and roof plate:

With foamed-in seal, removable

Mounting plate:

C-folded on the sides, depth-adjustable via integral plastic sliders in a 25 mm pitch pattern.

All screw-fastened cover parts with automatic potential equalisation and prepared for the attachment of earthing straps.

Accessories:

Side panels with foamed-in seal and assembly screws for finishing off the sides.

Protection category: IP 55

Material:

1.5 mm sheet steel, mounting plate of 3 mm sheet steel,

Data sheet



zinc-plated

Surface finish:

Electrophoretic dipcoat-primed

Outside surfaces powder-coated in textured RAL 7035

Dimensions (W x H x D): 1000 x 2000 x 500 mm