

Rittal – The System.

Faster – better – everywhere.

► Baying enclosure system VX25 Basic enclosure – VX 8215.000

Date : Aug 23, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Baying enclosure system VX25 Basic enclosure – VX 8215.000

created: 23.08.2018 on www.rittal.com/com-en



Product description

| | |
|--|--|
| Material: | Enclosure frame: Sheet steel, 1.5 mm Roof: Sheet steel, 1.5 mm Door: Sheet steel, 2.0 mm Rear panel: Sheet steel, 1.5 mm Gland plates: Sheet steel, 1.5 mm Mounting plate: Sheet steel 3.0 mm |
| Surface finish: | Enclosure frame: Dipcoat-primed Door, roof and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint |
| Colour: | RAL 7035 |
| Protection category IP to IEC 60 529: | IP 55 |
| Protection category NEMA: | NEMA 12 |
| IK Code: | IK10 |
| Supply includes: | Enclosure frame Door(s) Door hinged on the right, may be swapped to the left Roof plate Rear panel Gland plates Mounting plate 2 punched rails 18 x 39 mm Lock: 3 mm double-bit |
| Basic material: | Sheet steel |

Product features

Dimensions: Width: 1200 mm
Height: 1200 mm
Depth: 500 mm

Mounting plate: Width: 1099 mm
Height: 1096 mm

Number of doors: 2

Weight/pack: 140 kg

ETIM 5.0: EC000261

eCl@ss 8.0/8.1: 27180101

eCl@ss 6.0/6.1: 27180101

Product description (long): VX Baying enclosure system, WHD: 1200x1200x500 mm, sheet steel, with mounting plate, two doors at the front

Approvals

Approvals: CSA
Lloyds Register of Shipping
UL + C-UL

Certificates: IK-Code

Declarations: Declaration of conformity