

Rittal – The System.

Faster – better – everywhere.

► Baying enclosure system VX25, stainless steel Basic enclosure – VX 8457.000

Date : Jun 18, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Baying enclosure system VX25, stainless steel Basic enclosure – VX 8457.000

created: 18.06.2018 on www.rittal.com/com-en



Product description

Material: Enclosure frame: Stainless steel 1.4301 (AISI 304), 1.5 mm
Roof: Stainless steel 1.4301 (AISI 304), 1.5 mm, exterior brushed
Door: Stainless steel 1.4301 (AISI 304), 2.0 mm, exterior brushed
Rear panel: Stainless steel 1.4301 (AISI 304), 1.5 mm, exterior brushed
Gland plates: Stainless steel 1.4301 (AISI 304), 1.5 mm
Mounting plate: Sheet steel 3.0 mm

Surface finish: Enclosure frame and gland plates: Uncoated
Door, roof and rear panel: Exterior brushed, grain size 400
Mounting plate: Zinc-plated

**Protection category
IP to IEC 60 529:** IP 55

**Protection category
NEMA:** NEMA 12

IK Code: IK09

Supply includes: Enclosure frame
Door(s)
Door hinged on the right, may be swapped to the left
Roof plate
Gland plates
Rear panel
Mounting plate
Lock: 3 mm double-bit
2 punched rails 18 x 39 mm

Note: Due to the hardness of the material, we recommend using metal multi-tooth screws 2486.400 for the interior installation.

Product features

Dimensions:	Width: 600 mm Height: 1800 mm Depth: 500 mm
Mounting plate:	Width: 499 mm Height: 1696 mm
Number of doors:	1
Packs of:	1 pc(s).
Weight/pack:	92.5 kg
EAN:	4028177920187
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180101
Product description (long):	VX Baying enclosure system, WHD: 600x1800x500 mm, stainless steel, 1.4301, with mounting plate, single door at the front