

# Rittal – The System.

Faster – better – everywhere.

## ► Baying enclosure system VX25, stainless steel IP 66/NEMA 4X – VX 8458.000

Date : Jun 13, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Baying enclosure system VX25, stainless steel IP 66/NEMA 4X – VX 8458.000

created: 13.06.2018 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

<b>Material:</b>	Enclosure frame: Stainless steel 1.4301 (AISI 304), 1.5 mm Roof: Stainless steel 1.4301 (AISI 304), 1.5 mm, exterior brushed Door: Stainless steel 1.4301 (AISI 304), 2.0 mm, exterior brushed Rear panel: Stainless steel 1.4301 (AISI 304), 1.5 mm, exterior brushed Gland plate: Stainless steel 1.4301 (AISI 304), 1.5 mm Mounting plate: Sheet steel 3.0 mm
<b>Surface finish:</b>	Enclosure frame and gland plates: Uncoated Door, roof and rear panel: Exterior brushed, grain size 400 Mounting plate: Zinc-plated
<b>Protection category IP to IEC 60 529:</b>	IP 66
<b>Protection category NEMA:</b>	NEMA 4X
<b>Supply includes:</b>	Enclosure frame Door Door hinged on the right, may be swapped to the left Roof Base Rear panel Mounting plate Lock: 3 mm double-bit 2 punched rails 18 x 39 mm
<b>Note:</b>	Due to the hardness of the material, we recommend using metal multi-tooth screws 2486.400 for the interior installation.
<b>Basic material:</b>	Stainless steel

## Product features

**Dimensions:** Width: 800 mm  
Height: 2000 mm  
Depth: 600 mm

**Mounting plate:** Width: 699 mm  
Height: 1896 mm

**Number of doors:** 1

**Packs of:** 1 pc(s).

**Weight/pack:** 128.9 kg

**EAN:** 4028177924482

**Customs tariff number:** 94032080

**ETIM 6.0:** EC000261

**ETIM 5.0:** EC000261

**eCl@ss 8.0/8.1:** 27180101

**eCl@ss 7.0/7.1:** 27180101

**eCl@ss 6.0/6.1:** 27180101

**eCl@ss 5.1/5.1.4:** 27180101

**Product description (long):** VX Baying enclosure system IP66 / NEMA4x, WHD: 800x2000x600 mm, stainless steel, 1.4301, with mounting plate, sheet steel, zinc-plaed, single door at the front