

Data sheet

TS 8608.500



Main data:

Model No.:	TS 8608.500
Designation:	Top enclosure system, painted RAL 7035 with mounting plate, single-door
Variant:	mit Montageplatte, lackiert
Packs of:	1 ST
W x H x D:	600 mm x 2.000 mm x 800 mm
Mounting surface:	n/a
Volume:	1176,00 dm ³
Net weight:	105,74 kg
EAN:	4028177250956
Customs number:	85381000
Protection categories:	IP 55, NEMA 12

[You can find the product in Catalogue 32, page 146](#)

Approbationen:

BV	09639 / BO BV
CE	1 248 310
CE	1 333 701
CSA	LR 59132
DNV	E-8522
GL	15 644 - 00 HH
IP-Nema	Zertifikat
LR	07/20038
MRS	10.04048.250
TÜV	B 00 01 12010 115 de
TÜV	B 00 01 12010 115 engl
TÜV-MARK	Z30002 12010 116
UL	E 76083

Data sheet

TS 8608.500



VDE 6312 ÜG

Article features:

Material

Sheet steel
Enclosure frame, roof, rear panel and gland plates: 1.5 mm
Door: 2.0 mm
Mounting plate: 3.0 mm
Surface finish
Enclosure frame: Dipcoat-primed
Door, roof and rear panel:
Dipcoat-primed, powder-coated in textured RAL 7035 on the outside

Mounting plate and gland plates: Zinc-plated.
Supply includes
Enclosure frame with door, mounting plate, gland plates,
rear panel and

roof plate
Technical specifications
Dimensions:
Width: 600 mm
Height: 2000 mm
Depth: 800 mm
Door: 1
Weight: 111.3 kg

Texts for tenders:

Enclosure (baying system) single-door

Enclosure:

Symmetrical frame construction of rolled hollow sections with holes on a 25 mm DIN pitch pattern.

Data sheet

TS 8608.500



All sections have chamfered edges.
The horizontal sections have an additional protection lip above the seal.
The vertical sections have two mounting levels for space-saving interior installation.
Bayable on all sides.
Four eyebolts, three-piece gland plate can be removed and interchanged, fitted.

Door:

2 mm sheet steel, with foamed-in seal, with removable tubular door frame with holes on a 25 mm DIN pitch pattern, 4-point latch locking rod, double-bit insert to DIN 43668.

Door hinge may be swapped from right to left.
Hinges with captive hinge pins, door opening angle 130° to VDI, can be retrofitted to 180°, floor clearance 25 mm.

Rear panel and roof plate:

With foamed-in seal, removable

Mounting plate:

C-folded on the sides, depth-adjustable via integral plastic sliders in a 25 mm pitch pattern.
All screw-fastened cover parts with automatic potential equalisation and prepared for the attachment of earthing straps.

Accessories:

Side panels with foamed-in seal and assembly screws for

Data sheet

TS 8608.500



finishing off the sides.

Protection category: IP 55

Material:

1.5 mm sheet steel, mounting plate of 3 mm sheet steel,
zinc-plated

Surface finish:

Electrophoretic dipcoat-primed
Outside surfaces powder-coated in textured RAL 7035

Dimensions (W x H x D): 600 x 800 x 1200 mm