

Data sheet

TS 8610.600



Main data:

Model No.:	TS 8610.600
Designation:	Glazed door, aluminium, RAL 7035,
Variant:	n/a
Packs of:	1 ST
W x H x D:	600 mm x 2.000 mm x 0 mm
Mounting surface:	n/a
Volume:	122,00 dm ³
Net weight:	13,11 kg
EAN:	4028177211803
Customs number:	76101000
Protection categories:	n/a

Approbationen:

Article features:

Protection category to EN 60 529/10.91
IP 55
Lock system
With standard double-bit lock insert.
Double-bit insert can be exchanged for all lock inserts or
comfort

handles (in connection with handle adaptor)
Colour
Frame RAL 7035
Mask RAL 7015
Specifications
Frame: Extruded aluminium section, die-cast zinc corner
pieces,

Data sheet

TS 8610.600



Single-pane safety glass, 3 mm thick, printed mask on the inside, RAL

7015 (slate grey)
Locking rod with double-bit insert
180° hinges (4)

Material

Frame: Extruded aluminium section,
die-cast zinc corner pieces
Pane: Single-pane safety glass (ESG), 3 mm.
Dimensions mm W x H x D
For enclosures (WxH) = 600 x 2000 mm

Texts for tenders:

Glazed door for TS
Glazed door made of extruded aluminium section in RAL 7035, with foamed-in seal, 180° hinge, 3 mm thick single-pane safety glass, locking rod with four-point latching, with standard double-bit insert.
Double-bit insert can be exchanged for all lock inserts or comfort handles
(in connection with handle adaptor TS 8611.080).
Hinges with captive hinge pins, door hinge may be swapped from right to left without dismantling locking rods.

Material:

Frame: Sturdy extruded aluminium section,
die-cast zinc corner pieces.

Pane: Single pane safety glass (ESG), 3 mm

Colour:

Frame: RAL 7035

FRIEDHELM L O H GROUP

Data sheet

TS 8610.600



Printed mask on the inside of the pane: RAL 7015

Protection category to EN 60 529/10.91: IP 55

Dimensions:

For enclosures (WxH): W: 600 mm H: 2000 mm