

Rittal – The System.

Faster – better – everywhere.

► Glazed door for TS, TS IT, SE – TS 8610.605

Date : Apr 13, 2015

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Glazed door for TS, TS IT, SE – TS 8610.605

created : 13.04.2015 on www.rittal.com/com-en



Product description

Description: Instead of a sheet steel door or rear panel.

Material: Frame: Extruded aluminium section
Corner pieces: Die-cast zinc
Viewing window: Single-pane safety glass, 3 mm

Surface finish: Powder-coated

Colour: Frame: RAL 7035
Corner pieces: RAL 7035
Viewing window (printed mask on the inside): RAL 9005

**Protection category
IP to IEC 60 529:** IP 55

Assembly instruction: Lock components are required when mounting instead of the rear panel or double door.

Supply includes: Viewing door frame with safety glass
Locking rod with double-bit insert
180° hinges (4)

Packs of: 1 pc(s).

EAN: 4028177693845

eCl@ss 5.1: 27182201

eCl@ss 7.0: 27182290

Product features

To fit: Enclosure type: TS
Enclosure type: TS IT
Enclosure type: SE 8
Width: = 600 mm
Height: = 2000 mm

Viewing area: Width: 460 mm
Height: 1840 mm

Weight/PU: 15 kg

Downloads

Documentation:  [Instructions](#)
2 EN, DE

CAD drawings: Request