

Rittal – The System.

Faster – better – everywhere.

► Glazed door for TS, TS IT, SE – TS 8610.805

Date : Apr 13, 2015

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Glazed door for TS, TS IT, SE – TS 8610.805

created : 13.04.2015 on www.rittal.com/com-en



Product description

Description:	Instead of a sheet steel door or rear panel.
Material:	Frame: Extruded aluminium section Corner pieces: Die-cast zinc Viewing window: Single-pane safety glass, 3 mm
Surface finish:	Powder-coated
Colour:	Frame: RAL 7035 Corner pieces: RAL 7035 Viewing window (printed mask on the inside): RAL 9005
Protection category IP to IEC 60 529:	IP 55
Assembly instruction:	Lock components are required when mounting instead of the rear panel or double door.
Supply includes:	Viewing door frame with safety glass Locking rod with double-bit insert 180° hinges (4)
Packs of:	1 pc(s).
EAN:	4028177693852
eCl@ss 5.1:	27182201
eCl@ss 7.0:	27182290

Product features

To fit: Enclosure type: TS
Enclosure type: TS IT
Enclosure type: SE 8
Width: = 800 mm
Height: = 2000 mm

Viewing area: Width: 660 mm
Height: 1840 mm

Weight/PU: 18 kg

Downloads

Documentation:  [Instructions](#)
2 EN, DE

CAD drawings: Request