Rittal – The System.

Faster – better – everywhere.

Punched section with mounting flange, 18 x 64 mm for VX – VX 8617.010

Date : Jul 25, 2018



ENCLOSURES


POWER DISTRIBUTION 📎 CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Punched section with mounting flange, 18 x 64 mm for VX – VX 8617.010

created: 25.07.2018 on www.rittal.com/com-en



| Product description | n |
|-----------------------|--|
| Description: | For variable, individual interior installation of the enclosure frame on the outer mounting level. |
| Benefits: | Simply locate into the system punchings from the outside and screw-fasten. System punchings on all four sides. With pre-fitted side panels or bayed enclosures, the punched sections with mounting flanges may also be fitted from the inside of the enclosure. |
| Material: | Sheet steel |
| Surface finish: | Zinc-plated |
| Supply includes: | Assembly parts |
| Product features | |
| To fit: | Width/depth: 400 mm |
| Installation options: | On the outer mounting level, on the enclosure section On the outer mounting level, between two punched sections with mounting flanges 23 x 64 mm |
| Packs of: | 4 pc(s). |
| Weight/pack: | 1.59 kg |
| EAN: | 4028177829046 |

| Customs tariff number: | 94039010 |
|-----------------------------|---|
| ETIM 6.0: | EC002625 |
| ETIM 5.0: | EC002625 |
| eCl@ss 8.0/8.1: | 27189234 |
| eCl@ss 7.0/7.1: | 23159101 |
| eCl@ss 6.0/6.1: | 23159101 |
| eCl@ss 5.1/5.1.4: | 27189250 |
| Product description (long): | VX Punched section, with mounting flange 18 x 64 mm, for outer mounting level |