

Rittal – The System.

Faster – better – everywhere.

Punched section with mounting flange, 18 x 64 mm for VX – VX 8617.040

Date : Jul 25, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE


SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Punched section with mounting flange, 18 x 64 mm for VX – VX 8617.040

created: 25.07.2018 on www.rittal.com/com-en



Product description

Description:	For variable, individual interior installation of the enclosure frame on the outer mounting level.
Benefits:	Simply locate into the system punchings from the outside and screw-fasten. System punchings on all four sides. With pre-fitted side panels or bayed enclosures, the punched sections with mounting flanges may also be fitted from the inside of the enclosure.
Material:	Sheet steel
Surface finish:	Zinc-plated
Supply includes:	Assembly parts

Product features

To fit:	Width/depth: 800 mm
Installation options:	On the outer mounting level, on the enclosure section On the outer mounting level, between two punched sections with mounting flanges 23 x 64 mm
Packs of:	4 pc(s).
Weight/pack:	3.56 kg
EAN:	4028177829077

Customs tariff number:	94039010
ETIM 6.0:	EC002625
ETIM 5.0:	EC002625
eCl@ss 8.0/8.1:	27189234
eCl@ss 7.0/7.1:	23159101
eCl@ss 6.0/6.1:	23159101
eCl@ss 5.1/5.1.4:	27189250
Product description (long):	VX Punched section, with mounting flange 18 x 64 mm, for outer mounting level