

# Rittal – The System.

Faster – better – everywhere.

## ▶ TS isolator door cover (US version) – TS 8950.050

Date : Dec 11, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# TS isolator door cover (US version) – TS 8950.050

created: 11.12.2017 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

**Description:** Including main door lock for safety locking of enclosures and bayed enclosure suites in accordance with US regulations, only in conjunction with actuator lever for master switches.

**Benefits:** In combination with operating mechanism, adjacent door latch, interconnecting rods meets the requirements of UL 508 A. Compact design with a width of 125 mm, may be mounted optionally on the left or right of the enclosure. With this cover, all standard single-door TS 8 enclosures may be configured as isolator door enclosures. The complete installation surface of the enclosure is retained. In conjunction with the integrable TS mounting plate infill, the mounting surface of the main enclosure can be enlarged by around 100 mm in width. Cover may only be mounted on a single-door enclosure with tubular door frame

**Applications:** Allen Bradley: 1494 F-M1/P1/S1 and 140 U-K-FCX04  
Square D: 9422 A1  
General Electric: TDA Type 1 and 2  
Eaton NZM2(3)(4)-XSH-12-...-NA for type 4x  
Eaton NZM2(3)(4)-XSH-12-...-NA for type 12  
Siemens actuator for operating mechanism with bowden cable (Max-Flex drives) for moulded-case circuit-breakers 3VL UL:  
3VA9978-0CH72, epoxy-coated steel, printed with ON/OFF in red/black (also included with the scope of supply of complete Max-Flex kits 3VA9..8-0CK12)  
3VA9978-0CH82, chrome-plated steel, printed with ON/OFF in red/black  
3VA9978-0CH74, epoxy-coated steel, printed with ON/OFF in black/black  
3VL9600-3JP61, epoxy-coated steel, printed with ON/OFF in black/black  
Siemens actuator for operating mechanism with bowden cable (Max-Flex drives) for moulded-case circuit-breakers 3VL UL:  
3VL9600-3JP01, plastic, printed with ON/OFF in red/green (also included in scope of supply of complete Max-Flex kits 3VL9.00-3JM01)  
3VL9600-3JP21, epoxy-coated steel, printed with ON/OFF in red/black  
3VL9600-3JP41, chrome-plated steel, printed with ON/OFF in red/black  
3VL9600-3JP61, epoxy-coated steel, printed with ON/OFF in black/black  
Siemens actuator for operating mechanism with Bowden cable (Max-Flex drives) for SENTRON series circuit-breakers (ED, FD, LD, JD, ...) US model no.: FHOH, epoxy-coated steel, printed with ON/OFF in red/black

**Material:** Sheet steel

<b>Surface finish:</b>	Powder-coated
<b>Colour:</b>	RAL 7035
<b>Protection category IP to IEC 60 529:</b>	IP 55
<b>Protection category NEMA:</b>	NEMA 12
<b>Supply includes:</b>	Main door lock, cover plate and assembly parts.
<b>Note:</b>	The enclosure in front of the isolator door cover must be a single-door enclosure

## Product features

<b>Dimensions:</b>	Width: 125 mm Height: 2000 mm Depth: 500 mm
<b>Packs of:</b>	1 pc(s).
<b>Weight/pack:</b>	24.7 kg
<b>EAN:</b>	4028177693012
<b>Customs tariff number:</b>	85365019
<b>ETIM 6.0:</b>	EC000712
<b>ETIM 5.0:</b>	EC000261
<b>eCl@ss 8.0/8.1:</b>	27180101
<b>eCl@ss 7.0/7.1:</b>	27189290
<b>eCl@ss 6.0/6.1:</b>	27189290
<b>eCl@ss 5.1/5.1.4:</b>	27182101
<b>Product description (long):</b>	TS TS isolator door cover (US version), WHD: 100x1800x400 mm

## Approvals

<b>Approvals:</b>	UL + C-UL
<b>Certificates:</b>	EAC

---

**Declarations:**

Declaration of conformity

---