

Rittal – The System.

Faster – better – everywhere.

Busbar supports flat copper busbars – SV 9340.000

Date : Apr 22, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Busbar supports flat copper busbars – SV 9340.000

created : 22.04.2016 on www.rittal.com/com-en



Product description

Material:	Polyamide (PA 6.6) Fire protection corresponding to UL 94-V0
Colour:	RAL 7035
Note:	The use of a base tray is required for UL applications UL approval only applies in conjunction with AC application
Note on Model No.:	If 12 x 5/10 mm busbars are used, the spacer 9340.090 is additionally required
Packs of:	4 pc(s).
EAN:	4028177502321
Customs tariff number:	85469010
eCl@ss 5.1:	27370302
eCl@ss 7.0:	27400607
ETIM 6.0:	EC001166



Product features

To fit busbars:	Type: Flat copper busbars with cross-section width: 12 mm with cross-section width: 12 mm with cross-section width: 15 mm
------------------------	--

with cross-section width: 15 mm
 with cross-section width: 20 mm
 with cross-section width: 20 mm
 with cross-section width: 25 mm
 with cross-section width: 25 mm
 with cross-section width: 30 mm
 with cross-section width: 30 mm
 with cross-section height: 5 mm
 with cross-section height: 10 mm
 with cross-section height: 5 mm
 with cross-section height: 10 mm
 with cross-section height: 5 mm
 with cross-section height: 10 mm
 with cross-section height: 5 mm
 with cross-section height: 10 mm
 with cross-section height: 10 mm
 with cross-section height: 5 mm

Number of poles:	3-pole
Centre-to-centre spacing of busbars:	60 mm
Internal attachment:	yes
Weight/pack:	0.69 kg

Approvals

Approvals:	 Germanischer Lloyd (EN)
Declarations:	 Manufacturer's declaration (DE)

Downloads

Data sheets:	 Technical details EN
Characteristic curves:	 NA EN
Documentation:	 Instructions (EN, DE)  Safety instructions (DE, EN, FI, FR, NL, IT, PL, PT, SE, RU, ES, HU, SK)
CAD drawings:	Request