

Rittal – The System.

Faster – better – everywhere.

OM adaptors with connection cables – SV 9340.320

Date : Oct 25, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



OM adaptors with connection cables – SV 9340.320

created: 25.10.2016 on www.rittal.com/com-en



Product description

Material: Polyamide (PA 6.6)
Fire protection corresponding to UL 94-V0

Colour: Chassis: RAL 7035

Note: The technical data may vary for UL applications

Product features

To fit busbars: with cross-section height: 5 mm
with cross-section height: 10 mm

Number of poles: 3-pole

For bar systems with centre-to-centre spacing: 60 mm

Dimensions: Width: 45 mm
Height: 208 mm

Rated operating voltage: 690 V, 3~

Connection cable: Cross-section: AWG 12
Length: 130 mm

Rated current (max.): 25 A

Number of support 2

rails:

Height of support rails: 10 mm

Support rail type: TS 45D

Packs of: 1 pc(s).

Weight/pack: 0.26 kg

EAN: 4028177673823

Customs tariff number: 85369085

ETIM 6.0: EC001531

ETIM 5.0: EC001531

eCl@ss 8.0/8.1: 27370304

eCl@ss 7.0/7.1: 27370304

eCl@ss 6.0/6.1: 27370304

eCl@ss 5.1/5.1.4: 27370302

Approvals

Approvals: ABS
DNV GL
UL + C-UL

Declarations: Declaration of conformity