

Rittal – The System.

Faster – better – everywhere.

OM adaptors with connection cables – SV 9340.460

Date : Jun 2, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



OM adaptors with connection cables – SV 9340.460

created : 02.06.2016 on www.rittal.com/com-en



Product description

Material:	Polyamide (PA 6.6) Fire protection corresponding to UL 94-V0
Colour:	Chassis: RAL 7035
Note:	The technical data may vary for UL applications
Packs of:	1 pc(s).
EAN:	4028177502567
Customs tariff number:	85369085
eCl@ss 5.1:	27370302
eCl@ss 7.0:	27370304
ETIM 6.0:	EC001531

Product features

To fit busbars:	with cross-section height: 5 mm with cross-section height: 10 mm
Number of poles:	3-pole
For bar systems with	60 mm

**centre-to-centre
spacing:**

Dimensions:	Width: 55 mm Height: 208 mm
Rated operating voltage:	690 V, 3~
Connection cable:	Cross-section: AWG 10 Length: 130 mm
Support frame:	Width: 55 mm Height: 170 mm
Rated current (max.):	32 A
Number of support rails:	1
Height of support rails:	10 mm
Support rail type:	TS 55D
Weight/pack:	0.34 kg



Approvals

Approvals:  [C-UL \(EN\)](#)
 [Germanischer Lloyd \(EN\)](#)
 [UR + C-UR \(EN\)](#)

Declarations:  [Declaration of conformity \(EN, DE\)](#)
 [Manufacturer's declaration \(DE\)](#)

Downloads

Data sheets:  [Technical details](#)
EN

Documentation:  [Instructions \(FR, EN, DE\)](#)
 [Safety instructions \(DE, EN, FI, FR, NL, IT, PL, PT, SE, RU, ES, HU, SK\)](#)

CAD drawings: Request