

Rittal – The System.

Faster – better – everywhere.

Connection adaptors – SV 9342.240

Date : May 23, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Connection adaptors – SV 9342.240

created : 23.05.2016 on www.rittal.com/com-en



Product description


Material:	Cover: ABS Chassis: Polyamide (PA 6.6). Chassis 3439.010: Fibreglass-reinforced, thermoplastic polyester (PBT) Fire protection corresponding to UL 94-V0 Chassis: Polyamide (PA 6.6).
Colour:	RAL 7035
Note:	The technical data may vary for UL applications UL approval only applies in conjunction with AC application The rated operating voltage for DC applications depends on the busbar arrangement in the busbar support 9340.050/9341.050/9342.050.
Packs of:	1 pc(s).
EAN:	4028177522947
Customs tariff number:	85369010
eCl@ss 5.1:	27370302
eCl@ss 7.0:	27370304
ETIM 6.0:	EC001531

Product features

To fit busbars:	with cross-section height: 5 mm with cross-section height: 10 mm
------------------------	---

Number of poles:	3-pole
For bar systems with centre-to-centre spacing:	60 mm
Dimensions:	Width: 55 mm Height: 210 mm
Rated operating voltage:	690 V, 3~
Clamping area for laminated copper bars:	Width: 10 mm Height: 7.8 mm
Connection for round conductor cross-sections:	fine wire with wire end ferrule: 10 mm ² - 25 mm ² multi-wire: 16 mm ² - 35 mm ²
Rated current (max.):	125 A
Cable outlet:	Bottom
Weight/pack:	0.38 kg



Approvals

Approvals:  [C-UL \(EN\)](#)
 [UR + C-UR \(EN\)](#)

Declarations:  [Declaration of conformity \(EN, DE\)](#)
 [Manufacturer's declaration \(DE\)](#)

Downloads

Data sheets:  [Technical details](#)
EN

Documentation:  [Instructions \(EN, DE\)](#)
 [Safety instructions \(DE, EN, FI, FR, NL, IT, PL, PT, SE, RU, ES, HU, SK\)](#)

CAD drawings: Request