

Rittal – The System.

Faster – better – everywhere.

Connection adaptor – SV 9342.280

Date : Nov 4, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Connection adaptor – SV 9342.280

created: 04.11.2020 build on www.rittal.com/uk-en



Product description

Material: Cover: ABS
Punched section: Polyamide
Chassis 3439.010: Fibreglass-reinforced, thermoplastic polyester (PBT)
Fire protection corresponding to UL 94-V0
Punched section: Polyamide

Colour: RAL 7035

Note: The technical data may vary for UL applications
UL approval only applies in conjunction with AC application
The rated operating voltage for DC applications depends on the busbar arrangement in the busbar supports 9340.050/9341.050/9342.050.

Product features

To fit busbars: with cross-section height: 5 mm
with cross-section height: 10 mm

Number of poles: 3-pole

For bar systems with centre-to-centre spacing: 60 mm

Dimensions: Width: 129 mm
Height: 246 mm

Rated current max.: 800 A

Rated operating voltage: 690 V, 3~

Clamping area for laminated copper bars:	Width: 33 mm Height: 20 mm
Connection for round conductor cross-sections:	fine wire with wire end ferrule: 95 mm ² - 185 mm ² multi-wire: 95 mm ² - 300 mm ²
Cable outlet:	Top/bottom
Packs of:	1 pc(s).
Weight/pack:	2 kg
Copper weight (kg per piece):	0.36
EAN:	4028177503663
Customs tariff number:	85369010
ETIM 7.0:	EC001531
ETIM 6.0:	EC001531
eCl@ss 8.0/8.1:	27370304
eCl@ss 6.0/6.1:	27370304
Product description:	SV Connection adaptor, 800 A, 690 V, 3-pole, cable outlet top/bottom, round conductor connection 95-300 mm ² , clamping area WH: 33x20 mm
Approvals	
Approvals:	ABS C-UR DNV-GL Lloyds Register of Shipping
Certificates:	EAC
Declarations:	Declaration of conformity