

Rittal – The System.

Faster – better – everywhere.

Connection adaptor – SV 9342.300

Date : Sep 27, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Connection adaptor – SV 9342.300

created: 27.09.2018 on www.rittal.com/com-en



Product description

Material: Cover: ABS
Chassis: Polyamide (PA 6.6).
Chassis 3439.010: Fibreglass-reinforced, thermoplastic polyester (PBT)
Fire protection corresponding to UL 94-V0
Chassis: Polyamide (PA 6.6).

Colour: RAL 7035

Note: The technical data may vary for UL applications
UL approval only applies in conjunction with AC application
The rated operating voltage for DC applications depends on the busbar arrangement in the busbar support 9340.050/9341.050/9342.050.

Product features

To fit busbars: with cross-section height: 5 mm
with cross-section height: 10 mm

Number of poles: 3-pole

For bar systems with centre-to-centre spacing: 60 mm

Dimensions: Width: 129 mm
Height: 246 mm

Clamping area for laminated copper bars: Width: 33 mm
Height: 20 mm

Connection for round conductor cross- fine wire with wire end ferrule: 95 mm² - 185 mm²
multi-wire: 95 mm² - 300 mm²

sections:

Rated current (max.):	800 A
Cable outlet:	Bottom
Packs of:	1 pc(s).
Weight/pack:	1.56 kg
EAN:	4028177503687
Customs tariff number:	85369010
ETIM 6.0:	EC001531
ETIM 5.0:	EC001531
eCl@ss 8.0/8.1:	27370304
eCl@ss 7.0/7.1:	27370304
eCl@ss 6.0/6.1:	27370304
eCl@ss 5.1/5.1.4:	27370302
Product description (long):	SV Connection adaptor, 800 A, 690 V, 3-pole, cable outlet bottom, round conductor connection 95-300 mm ² , clamping area WH: 33x20 mm
Approvals	
Approvals:	ABS C-UL DNV-GL Lloyds Register of Shipping UL + C-UL
Certificates:	EAC
Declarations:	Declaration of conformity