

Rittal – The System.

Faster – better – everywhere.

▶ NH fuse-switch- disconnectors, size 00 to 3 with electromechanical fuse monitoring – SV 9343.150

Date : Nov 21, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



NH fuse-switch-disconnectors, size 00 to 3 with electromechanical fuse monitoring – SV 9343.150

created: 21.11.2016 on www.rittal.com/com-en



Product description

Material: Polyamide (PA 6)
Fire protection corresponding to UL 94-V0
Contact tracks: Electrolytic copper, silver-plated

Colour: Chassis: RAL 7035
Cover: RAL 7035/7001

Basis of test: IEC/DIN EN 60 947-3
DIN EN 60 269-2 (fuse inserts)

Product features

Design: Size: 1

To fit busbars: with cross-section height: 5 mm
with cross-section height: 10 mm

Number of poles: 3-pole

For bar systems with centre-to-centre spacing: 60 mm

Dimensions: Width: 184 mm
Height: 298 mm

Type of electrical connection: Screw M10

Rated operating voltage:	690 V, 3~
Clamping area for laminated copper bars:	Width: 32 mm Height: 10 mm
Connection for round conductor cross-sections:	10 mm ² - 150 mm ²
Rated operating current max.:	250 A
Cable outlet:	Top/bottom
Packs of:	1 pc(s).
Weight/pack:	2.8 kg
EAN:	4028177540378
Customs tariff number:	85369085
ETIM 6.0:	EC001040
ETIM 5.0:	EC001040
eCl@ss 8.0/8.1:	27371401
eCl@ss 7.0/7.1:	27371401
eCl@ss 6.0/6.1:	27371401
eCl@ss 5.1/5.1.4:	27370302
Approvals	
Declarations:	Declaration of conformity