

Rittal – The System.

Faster – better – everywhere.



SV 9343.210

NH fuse-switch-disconnectors, size 00 to 3

State: 28/02/2022 (Source: rittal.com/com-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 9343.210 - NH fuse-switch-disconnectors, size 00 to 3

Features

Material	Polyamide Fire protection corresponding to UL 94 Contact tracks: Electrolytic copper, silver-plated
Colour	Chassis: RAL 7035 Cover: RAL 7035/7001
Clamping area for laminated copper bars	Width: 50 mm Height: 10 mm
For busbar systems with centre-to-centre spacing	60 mm
Cable outlet	Top/bottom
Type of electrical connection	Screw M10
Rated operating current (max.)	400 A
NH construction size	2
Note	The technical data may vary for UR applications. Applications to UR only in conjunction with "Special Purpose Fuses".
Test specification	IEC/DIN EN 60 947-3 DIN EN 60 269-2 (fuse inserts)
Dimensions	Width: 210 mm Height: 298 mm
Connection for round conductor cross-sections	10 - 240 mm ²
To fit busbars	with cross-section height: 5, 10 mm
Rated operating voltage	690 V, 3~
Number of poles	3-pole
Weight/pack	3.36 kg
Packs of	1 Stück

Features

ETIM 7.0	EC001040
----------	----------

ECLASS 8.0	27371401
------------	----------

Approvals

Approvals	C-UR CQC-CCC UR + C-UR
-----------	------------------------------

Certificates	EAC
--------------	-----

Explanations	Declaration of conformity
--------------	---------------------------