

Rittal – The System.

Faster – better – everywhere.



SV 9343.310

**NH fuse-switch-disconnectors, size
00 to 3**

State: 28/03/2022 (Source: rittal.com/com-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 9343.310 - NH fuse-switch-disconnectors, size 00 to 3



Features

Model No.	SV 9343.310
Material	Polyamide Fire protection corresponding to UL 94 Contact tracks: Electrolytic copper, silver-plated
Colour	Chassis: RAL 7035 Cover: RAL 7035/7001
Clamping area for laminated copper bars	Width: 50 mm Height: 10 mm
For busbar systems with centre-to-centre spacing	60 mm
Cable outlet	Top/bottom
Type of electrical connection	Screw M10
Rated operating current (max.)	630 A
NH construction size	3
Note	The technical data may vary for UR applications. Applications to UR only in conjunction with "Special Purpose Fuses".
Test specification	IEC/DIN EN 60 947-3 DIN EN 60 269-2 (fuse inserts)
Dimensions	Width: 250 mm Height: 298 mm

Features

Connection for round conductor cross-sections	10 - 300 mm ²
To fit busbars	with cross-section height: 5, 10 mm
Rated operating voltage	690 V, 3~
Number of poles	3-pole
Packs of	1 pc(s).
Weight/pack	4.22 kg
Copper weight (kg per piece)	1.44
Customs tariff number	85369095
EAN	4028177540453
ETIM 7.0	EC001040
ECLASS 8.0	27371401

Approvals

Approvals	C-UR CQC-CCC UR + C-UR
Certificates	EAC
Explanations	Declaration of conformity
