

Rittal – The System.

Faster – better – everywhere.

NH fuse-switch- disconnectors, size 00 to 3 – SV 9344.000

Date : May 20, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



NH fuse-switch-disconnectors, size 00 to 3 – SV 9344.000

created : 20.05.2016 on www.rittal.com/com-en




Product description

Material:	Polyamide (PA 6) Fire protection corresponding to UL 94-V0 Contact tracks: Electrolytic copper, silver-plated
Colour:	Chassis: RAL 7035 Cover: RAL 7035/7001
Basis of test:	IEC/DIN EN 60 947-3 DIN EN 60 269-2 (fuse inserts)
Note:	The technical data may vary for UR applications. Applications to UR only in conjunction with "Special Purpose Fuses".
Packs of:	1 pc(s).
EAN:	4028177540507
Customs tariff number:	85369085
eCl@ss 5.1:	27370302
eCl@ss 7.0:	27371401
ETIM 6.0:	EC001040

Product features

Design:	Size: 00
Number of poles:	3-pole
For mounting plate assembly:	yes
Dimensions:	Width: 106 mm Height: 194 mm
Type of electrical connection:	Box terminal
Rated operating voltage:	690 V, 3~
Clamping area for laminated copper bars:	Width: 13 mm Height: 13 mm
Connection for round conductor cross-sections:	4 mm ² - 95 mm ²
Rated operating current max.:	160 A
Cable outlet:	Top/bottom
Weight/pack:	0.76 kg


Approvals

Approvals:  [C-UR \(EN\)](#)
 [UR \(EN\)](#)

Declarations:  [Declaration of conformity \(EN, DE\)](#)
 [Manufacturer's declaration \(DE\)](#)

Downloads

Data sheets:  [Technical details](#)
EN

Documentation:  [Safety instructions \(DE, EN, FI, FR, NL, IT, PL, PT, SE, RU, ES, HU, SK\)](#)

CAD drawings: Request