

# Rittal – The System.

Faster – better – everywhere.

## Fuse holders 61 A to 400 A – SV 9345.200

Date : Oct 14, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Fuse holders 61 A to 400 A – SV 9345.200

created: 14.10.2020 build on [www.rittal.com/uk-en](http://www.rittal.com/uk-en)



## Product description

**Material:** Polyamide  
Fire protection corresponding to UL 94-V0  
Contact tracks: Electrolytic copper, silver-plated

**Colour:** Chassis: RAL 7035  
Cover: RAL 7035/7001

**Standards:** UL 508

**Note:** UL (listed accessory) is met when using the fuse holder on RiLine busbar systems

## Product features

**To fit busbars:** with cross-section height: 5 mm  
with cross-section height: 10 mm

**Number of poles:** 3-pole

**For bar systems with centre-to-centre spacing:** 60 mm

**Dimensions:** Width: 210 mm  
Height: 288 mm

**Type of electrical connection:** Box terminal

**Rated operating voltage:** 600 V, 3~

**Connection for round** AWG 4/0 – MCM 600

**conductor cross-sections:**

<b>Rated operating current min.:</b>	101 A
<b>Rated operating current max.:</b>	200 A
<b>Cable outlet:</b>	Top/bottom
<b>To fit fuses:</b>	Fuse type (class): J Fuse standard: UL 248-8 Ø x length: 41 mm x 146 mm
<b>Packs of:</b>	1 pc(s).
<b>Weight/pack:</b>	3.94 kg
<b>Copper weight (kg per piece):</b>	1.39
<b>EAN:</b>	4028177615663
<b>Customs tariff number:</b>	85365080
<b>ETIM 7.0:</b>	EC001900
<b>ETIM 6.0:</b>	EC001900
<b>eCl@ss 8.0/8.1:</b>	27400613
<b>eCl@ss 6.0/6.1:</b>	27400613
<b>Product description:</b>	SV Fuse holder, Class J, 101-200 A, 600 V, 3-pole, (60 mm)
<b>Approvals</b>	
<b>Approvals:</b>	C-UR UL + C-UL UR
<b>Certificates:</b>	EAC