

# Rittal – The System.

Faster – better – everywhere.

## Fuse holders 61 A to 400 A – SV 9345.400

Date : Jan 18, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Fuse holders 61 A to 400 A – SV 9345.400

created: 18.01.2018 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

|                  |   |
|------------------|---|
| <b>Design:</b>   | For busbar systems  |
| <b>Material:</b> | Polyamide (PA 6)<br>Fire protection corresponding to UL 94-V0<br>Contact tracks: Electrolytic copper, silver-plated |
| <b>Colour:</b>   | Chassis: RAL 7035<br>Cover: RAL 7035/7001   |
| <b>Note:</b>     | UL (listed accessory) is met when using the fuse holder on RiLine busbar systems                                    |

## Product features

|   |   |
|---|---|
| <b>To fit busbars:</b>                                | with cross-section height: 5 mm<br>with cross-section height: 10 mm |
| <b>Number of poles:</b>                               | 3-pole  |
| <b>For bar systems with centre-to-centre spacing:</b> | 60 mm   |
| <b>Dimensions:</b>                                    | Width: 250 mm<br>Height: 328 mm                                     |
| <b>Type of electrical connection:</b>                 | Box terminal  |
| <b>Rated operating voltage:</b>                       | 600 V, 3~   |

|   |  |
|---|--|
| <b>Connection for round conductor cross-sections:</b> | AWG 4/0 – MCM 600  |
| <b>Rated operating current min.:</b>                  | 201 A  |
| <b>Rated operating current max.:</b>                  | 400 A  |
| <b>Cable outlet:</b>                                  | Top/bottom   |
| <b>To fit fuses:</b>                                  | Fuse type (class): J<br>Fuse standard: UL 4248-8<br>Ø x length: 54 mm x 181 mm |
| <b>Packs of:</b>                                      | 1 pc(s).   |
| <b>Weight/pack:</b>                                   | 5.32 kg  |
| <b>EAN:</b>   | 4028177615670  |
| <b>Customs tariff number:</b>                         | 85365080   |
| <b>ETIM 6.0:</b>                                      | EC001900   |
| <b>ETIM 5.0:</b>                                      | EC001900   |
| <b>eCl@ss 8.0/8.1:</b>                                | 27400613   |
| <b>eCl@ss 7.0/7.1:</b>                                | 27400613   |
| <b>eCl@ss 6.0/6.1:</b>                                | 27400613   |
| <b>eCl@ss 5.1/5.1.4:</b>                              | 27370302   |
| <b>Product description (long):</b>                    | SV Fuse holder, Class J, 201-400 A, 600 V, 3-pole, (60 mm)                     |
| <b>Approvals</b>                                      |  |
| <b>Approvals:</b>                                     | C-UR<br>UL + C-UL<br>UR  |
| <b>Certificates:</b>                                  | EAC  |