

Rittal – The System.

Faster – better – everywhere.

Polycarbonate enclosures PK without knockouts – PK 9502.000

Date : Aug 3, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Polycarbonate enclosures PK without knockouts – PK 9502.000

created: 03.08.2020 build on www.rittal.com/uk-en



Product description

Applications:	Ambient temperature range: -35 °C...+80 °C The specified temperatures may be limited by the installed equipment
Material:	Housing: Fibre-glass reinforced polycarbonate Cover grey: Fibreglass-reinforced polycarbonate, all-round foamed-in PU seal Cover screws: Polyamide Insulating bungs: Polyethylene
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4X
Supply includes:	Enclosure with cover Cover screws Insulating bungs for wall mounting screws
Basic material:	Polycarbonate

Product features

Dimensions:	Width: 94 mm Height: 65 mm Depth: 57 mm
Cover:	grey

Ambient temperature range:	-35 °C...+80 °C
Packs of:	8 pc(s).
Weight/pack:	1.1 kg
EAN:	4028177139015
Customs tariff number:	94037000
ETIM 7.0:	EC000261
ETIM 6.0:	EC000261
eCl@ss 6.0/6.1:	27180101
Product description:	PK Polycarbonate enclosure, WHD: 94x65x57 mm, fibreglass-reinforced polycarbonate, without knockouts, with grey cover
Approvals	
Approvals:	C-UL DNV-GL UL UL + C-UL
Certificates:	EAC
Declarations:	Declaration of conformity