

Rittal – The System.

Faster – better – everywhere.

Polycarbonate enclosures PK without knockouts – PK 9517.000

Date : Jun 17, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Polycarbonate enclosures PK without knockouts – PK 9517.000

created: 17.06.2016 on www.rittal.com/com-en



Product description

Material: Housing: Fibre-glass reinforced polycarbonate
Cover screws: Polyamide
Insulating bungs: Polyethylene
Cover grey: Fibreglass-reinforced polycarbonate, all-round foamed-in PU seal

Colour: RAL 7035

**Protection category
IP to IEC 60 529:** IP 66

**Protection category
NEMA:** NEMA 4X

Supply includes: Enclosure with cover
Cover screws
Insulating bungs for wall mounting screws

Packs of: 1 pc(s).






EAN: 4028177139619

**Customs tariff
number:** 94037000

eCl@ss 5.1: 27180102

eCl@ss 7.0: 27180101

ETIM 6.0: EC000261

Basic material:	Polycarbonate
Product features	
Dimensions:	Width: 182 mm Height: 180 mm Depth: 90 mm
Cover:	grey
Ambient temperature range:	-35°C...+80°C
Note:	The specified temperatures may be limited by the installed equipment
Operating temperature (max.):	80 °C
Weight/pack:	0.6 kg
Approvals	
Approvals:	 Bureau Veritas (EN)  C-UL (EN)  UL (EN)
Declarations:	 Declaration of conformity (DE)
Downloads	
Data sheets:	 Technical details EN
CAD drawings:	Request