

# Rittal – The System.

Faster – better – everywhere.

## Polycarbonate enclosures PK without knockouts – PK 9524.100

Date : Jun 16, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Polycarbonate enclosures PK without knockouts – PK 9524.100

created: 16.06.2016 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

**Material:** Housing: Fibre-glass reinforced polycarbonate  
Cover screws: Polyamide  
Insulating bungs: Polyethylene  
Cover transparent: Polycarbonate, all-round foamed-in PU seal

**Colour:** RAL 7035

**Protection category  
IP to IEC 60 529:** IP 66

**Protection category  
NEMA:** NEMA 4X

**Supply includes:** Enclosure with cover  
Cover screws  
Insulating bungs for wall mounting screws

**Packs of:** 1 pc(s).






**EAN:** 4028177139916

**Customs tariff  
number:** 94037000

**eCl@ss 5.1:** 27180102

**eCl@ss 7.0:** 27180101

**ETIM 6.0:** EC000261

<b>Basic material:</b>	Polycarbonate
<b>Product features</b>	
<b>Dimensions:</b>	Width: 360 mm Height: 254 mm Depth: 165 mm
<b>Cover:</b>	transparent
<b>Ambient temperature range:</b>	-35°C...+80°C
<b>Note:</b>	The specified temperatures may be limited by the installed equipment
<b>Operating temperature (max.):</b>	80 °C
<b>Weight/pack:</b>	1.9 kg
<b>Approvals</b>	
<b>Approvals:</b>	 <a href="#">Bureau Veritas (EN)</a>  <a href="#">C-UL (EN)</a>  <a href="#">UL (EN)</a>
<b>Declarations:</b>	 <a href="#">Declaration of conformity (DE)</a>
<b>Downloads</b>	
<b>Data sheets:</b>	 <a href="#">Technical details</a> EN
<b>CAD drawings:</b>	Request