


Data sheet

SV 9661.040



Main data:


Model No.:	SV 9661.040
Designation:	Busbar E-Cu, 40x10 mm, length 392 mm, for enclosure width 400 mm
Variant:	n/a
Packs of:	2 ST
BxHxT:	k.A.
Mounting surface:	n/a
Volume:	0,20 dm ³
Net weight:	2,75 kg
EAN:	4028177555761
Customs number:	74071000
Protection categories:	n/a

Article features:

Application
The PE/PEN combination, comprising busbars, combination angles and baying brackets, supports type-tested configurations as per IEC 60 439-1. Thanks to the pre-assembled combination angles, baying brackets and busbars customised to match the enclosure width, assembly is time-saving with cost reduction.

Data sheet

SV 9661.040



Technical specifications

Tested short-circuit resistance

- PE/PEN combination

30 x 5 mm is:

I_{cw} 18 kA, 1 sec

- PE/PEN combination

30 x 10 mm is:

I_{cw} 30 kA, 1 sec

- PE/PEN combination

40/80 x 10 mm:

I_{cw} 30 kA, 1 sec;

I_{cw} 42 kA, 1 sec (when
mounted on blank section
frames)

For enclosure width: 400 mm

Length: 392 mm

Material

E-Cu