

Rittal – The System.

Faster – better – everywhere.

Plastic enclosures KS – KS 1469.500

Date : Jan 20, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Plastic enclosures KS – KS 1469.500

created: 20.01.2020 build on www.rittal.com/uk-en



Product description

Design: With viewing window

Material: Enclosure and door: Fibreglass-reinforced unsaturated polyester
Door: All-round foamed-in PU seal
Mounting plate: Sheet steel
Viewing window: Glazed acrylic, 3.0 mm with all-round rubber cable clamp strip

Surface finish: Enclosure and door: Dyed plastic with no after-treatment
Mounting plate: Zinc-plated

Colour: Similar to RAL 7035

**Protection category
IP to IEC 60 529:** IP 56

**Protection category
NEMA:** NEMA 12

IK Code: IK08

Supply includes: Enclosure with hinged door, of all-round solid construction, 3 mm double-bit lock
Mounting plate
Twin seal on the top and bottom edges of the door as integral rain protection strip
Press-fitted C sections at the sides for infinitely variable mounting plate depth adjustment
Viewing window in the door

Note: Under the influence of long-term UV radiation (sunlight) in conjunction with wind and rain, the surface finish may become visually impaired. This does not affect the protection of the installed electrical components in any way. If the enclosures cannot be protected from UV radiation, we recommend that they should be painted with a PUR paint. Ambient temperature -30 °C...+75 °C.

Basic material: Plastic

Product features

Dimensions: Width: 600 mm
Height: 800 mm
Depth: 300 mm

Viewing window: yes

Material thickness: Mounting plate: 3 mm

Mounting plate: Width: 517 mm
Height: 750 mm

Number of doors: 1

Door hinged on the right, may be swapped to the left: yes

Lock version: 3-point lock system

Number of locks: 1

Lock insert: 3 mm double-bit

Packs of: 1 pc(s).

Weight/pack: 26 kg

EAN: 4028177526785

Customs tariff number: 94037000

ETIM 7.0: EC000261

ETIM 6.0: EC000261

eCl@ss 8.0/8.1: 27180101

eCl@ss 6.0/6.1: 27180101

Product description: KS Plastic enclosure, WHD: 600x800x300 mm, Fibreglass-reinforced unsaturated polyester, with mounting plate, with door, viewing window

Approvals

Approvals: Bureau Veritas
Germanischer Lloyd
Lloyds Register of Shipping
Russian Maritime Register of Shipping
TÜV

Certificates: EAC
IK-Code
Protection category

Declarations: Declaration of conformity
