



<http://www.ruebsamen-und-herr.de/english>

04.11.2004 / 11:15 Uhr

### Enclosure heaters

- For the compensation of temperature variations inside the cabinet
- Avoidance of water condensation
- Equipped with either wire resistor or self-regulating PTC heating element
- Output ranges from 10 to 400 W



### VARIANTS:

| Type           | Configuration                | Thermal output at 20°C | Voltage                      | Dimensions (W x H x D) |
|----------------|------------------------------|------------------------|------------------------------|------------------------|
| <b>SH 10</b>   | PTC heating element          | 10W                    | 110 – 240V AC/DC             | 50 x 28 x 50 mm        |
| <b>SH 20</b>   | PTC heating element          | 20W                    | 110 – 240V<br>12 – 24V AC/DC | 70 x 28 x 50 mm        |
| <b>SH 30</b>   | PTC heating element          | 30W                    | 110 – 240V<br>12 – 24V AC/DC | 90 x 28 x 50 mm        |
| <b>SH 45</b>   | PTC heating element          | 45W                    | 110 – 240V AC/DC             | 150 x 28 x 50 mm       |
| <b>SH 60</b>   | PTC heating element          | 60W                    | 110 – 240V<br>12 – 24V AC/DC | 105 x 80 x 80 mm       |
| <b>SH 75</b>   | PTC heating element          | 75W                    | 110 – 240V AC/DC             | 155 x 80 x 80 mm       |
| <b>SH 100</b>  | PTC heating element          | 100W                   | 110 – 240V AC/DC             | 185 x 80 x 80 mm       |
| <b>SH 150</b>  | PTC heating element          | 150W                   | 110 – 240V AC/DC             | 245 x 80 x 80 mm       |
| <b>SH 250L</b> | PTC heating element with fan | 250W                   | 115 oder 230 V<br>50/60 Hz   | 155 x 80 x 80 mm       |
| <b>SH 400L</b> | PTC heating element with fan | 400W                   | 115 oder 230 V<br>50/60 Hz   | 235 x 80 x 80 mm       |
| <b>RH 35</b>   | invariable resistor          | 35W                    | 400 V<br>AC/DC               | 130 x 72 x 50 mm       |
| <b>RH 55</b>   | invariable resistor          | 45W                    | 400 V<br>AC/DC               | 165 x 72 x 50 mm       |
| <b>SH 75D</b>  | invariable resistor          | 70W                    | 400 V<br>AC/DC               | 185 x 80 x 80 mm       |
| <b>SH 100D</b> | invariable resistor          | 100W                   | 400 V<br>AC/DC               | 215 x 80 x 80 mm       |

**For additional Information please contact:**

**Rübsamen & Herr Elektrobau GmbH**  
**Am Scheid 4**  
**57290 Neunkirchen, Siegerl.**  
**e-mail: [info@ruebsamen-und-herr.de](mailto:info@ruebsamen-und-herr.de)**  
**<http://www.ruebsamen-und-herr.de/english>**

© Copyright by [MC<sup>2</sup> MARKETING & COMMUNICATION](#), created with [FIRMATIC](#) - professional e-Marketing.