

## Datasheet - EFK30.3



Command and signalling devices / Contact and light terminal blocks (EF/EL) System / contact elements / contact element EF - (N)

- Cage clamps
- Mounting flange position 3
- 31-32 (Contact labelling)
- Suitable for EMERGENCY-OFF



(Minor differences between the printed image and the original product may exist!)

### Ordering details

Product type description	EFK30.3
Article number	101026059
Strobe lamp	
eCl@ss	27-37-13-02

### Approval

Approval



### Global Properties

Permanent light	Kontaktelement EFK
Standards	IEC/EN 60947-1, EN 60947-5-1
Compliance with the Directives (Y/N)	Yes
Contact labelling	31-32
Materials	
- Material of the housings	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
- Material of the contacts	Silver
Weight	20
Suitable for EMERGENCY-OFF (Y/N)	Yes

## Mechanical data

---

Connection type	Cage clamps, WAGO Cage Clamp
notice	All indications about the cable section are including the conductor ferrules.
Cable section	
- Min. Cable section	2 x 0,08
- Max. Cable section	2 x 1.5
Assembly	pluggable
Mounting flange position	3
Mechanical life / contact element	10.000.000 operations
Switching frequency	1200
restistance to shock	110 / 4
resistant to vibration	> 20 / 10 ... 200
Bounce duration (100 /)	< 5
positive break travel	2
Contact opening	3

## Ambient conditions

---

Ambient temperature	
- Min. environmental temperature	-25
- Max. environmental temperature	+80
Protection class	
- Protection class-Terminals	IP20
- Protection class switching compartments	IP40

## Electrical data

---

Design of control element	Opener (NC)
Switching principle	Slow action
Number of shutters	0
Number of openers	1
Rated insulation voltage	400
Thermal test current	10 A
Utilisation category	AC-15: 230 V / 8 A DC-13: 24 V / 5 A
Max. fuse rating	10 A gG D-fuse slow blow
Test voltage (enclosed)	2500
Suitable for low-voltages	≥ 5 , 3.2

## Dimensions

---






Dimensions	
- Width	10
- Length	46
- Depth	51

## Switch travel diagram

---



Notes Switch travel diagram

-  Contact closed
  -  Contact open
  -  Setting range
  -  Break point
  -  Positive opening sequence/- angle
- VS** adjustable range of NO contact  
**VÖ** adjustable range of NC contact  
**N** after travel

## Documents

---

**CCC certification** (en) 1 MB, 20.06.2017

Code: q\_efelp02

**CCC certification** (cn) 1 MB, 20.06.2017



Code: q\_efelp03

**EAC certification** (ru) 779 kB, 05.10.2015

Code: q\_6043p17\_ru


## Images

---



Application

---



Operating principle

---

