

## Datasheet - NBG 632/NM

Command and signalling devices / Assembly housing NBG / NBG



- for application in food producing machinery
- Enclosure seal for food machinery

(Minor differences between the printed image and the original product may exist!)

### Ordering details

Product type description	NBG 632/NM
Article number	101182350
Strobe lamp	
eCl@ss	27-37-12-05

### Approval

Approval



### Global Properties

Permanent light	NBG - Aufbaugehäuse
Number of command positions	2
Materials	
- Material of the housings	Stainless steel (V4A)
- Housing color of upper part	■ Silver
- color of base part	■ Silver
Color	
- Colour of the bellows	Grey
Weight	1250
Number of through-holes for the cable gland	1
Protective collar in housing cover (Y/N)	No

### Mechanical data

Knockout holes for cable gland (Y/N)	No
Position of the cable gland	mounting holes

### Ambient conditions

Ambient temperature	
- Min. environmental temperature	-25
- Max. environmental temperature	+80
Protection class	IP67, IP69K

## Dimensions

---

### Dimensions

- Width	110
- Height	86.5
- Depth	204
Diameter of the through-holes for cable glands	20.3
Center-to-center distance of the drilled holes for the command posts	84

## notice

---

notice

Hygiene-compliant IP69 cable gland in 1.4305 upon request

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 11.01.2018 - 14:33:13h Kasbase 3.3.0.F.64I