

### Main

Range of product	Advantys FTM
Product or component type	IP67 modular I/O splitter box
Splitter box type	Expandable
Input/Output number	8
Discrete input number	8
Product compatibility	With 2-wire/3-wire sensors
Electrical connection	1 female connector M12 next module 1 male connector M12 bus module or previous module 8 female connectors M8 sensor

### Complementary

Internal current consumption	30 mA
[Ue] rated operational voltage	24 V DC
Supply current	≤ 4 A
Discrete input voltage	24 V
Discrete input voltage type	DC
Discrete input current	200 mA
Discrete input logic	Positive
Sensor power supply	18...30 V
Reverse polarity protection	Internal
Input filtering	1 ms
Control threshold undervoltage	0...18 V
Status LED	1 LED per channel yellow channel status 1 LED per channel power ON
Surge withstand	-1 kV signal conforming to IEC 61000-4-5 0.5 kV power supply conforming to IEC 61000-4-5 0.5 kV ground/PE conforming to IEC 61000-4-5 1 kV signal conforming to IEC 61000-4-5
Operating position	Any position
Fixing mode	By 2 screws
Tightening torque	1.5 N.m , M4 screw(s)
Product weight	0.12 kg

### Environment

Standards	IEC 1131-2 Type 2
Product certifications	CULus
Ambient air temperature for operation	0...55 °C
Ambient air temperature for storage	-25...70 °C
IP degree of protection	IP67
Operating altitude	0...2000 m
Vibration resistance	15 gn conforming to IEC 68-2-6
Shock resistance	50 gn , for 11 ms conforming to IEC 68-2-27, EA tests
Resistance to electrostatic discharge	-8 kV in air conforming to IEC 61000-4-2 -4 kV in contact conforming to IEC 61000-4-2 4 kV in contact conforming to IEC 61000-4-2 8 kV in air conforming to IEC 61000-4-2
Resistance to radiated fields	10 V/m conforming to IEC 61000-4-3

Resistance to fast transients	-2 kV power supply conforming to IEC 61000-4-4 -2 kV signal conforming to IEC 61000-4-4 2 kV power supply conforming to IEC 61000-4-4 2 kV signal conforming to IEC 61000-4-4
Resistance to conducted disturbances, induced by radio frequency fields	10 V conforming to IEC 61000-4-6
Resistance to magnetic fields	30 A/m , 50 Hz conforming to IEC 61000-4-8
RoHS EUR conformity date	0608
RoHS EUR status	Compliant