Product datasheet Characteristics

GV2G254

Linergy FT - Comb busbar - 63 A - 2 tap-offs - 54 mm pitch



Price*: 7.95 GBP



Main

		4
Range	Linergy	
Product name	FT	
Device short name	GV2G	ў — ў — ў — ў — ў — ў — ў — ў — ў — ў —
Product or component type	Comb busbar).
Accessory / separate part category	Connection accessory	
Poles description	3P	
Range compatibility	TeSys - GV2 TeSys - U TeSys - D TeSys - K	minion
Number of tap-offs	2	i d
[lth] conventional free air thermal current	63 A	5 E
Connection pitch	54 mm	

Complementary

Mounting location	On terminal	•
[Ui] rated insulation voltage	690 V	Ţ.
Length	108 mm	
2011941		9
Product weight	0.038 kg	ž
i roduct weight	0.000 kg	9


Offer Sustainability

<u> </u>		
Sustainable offer status	Green Premium product	tation—
RoHS (date code: YYWW)	Compliant - since 0640 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	io Op
REACh	Reference not containing SVHC above the threshold	Ę
	Reference not containing SVHC above the threshold	e E.


Product environmental profile	Available Product Environmental Profile	
Product end of life instructions	Need no specific recycling operations	
Contractual warranty		
Warranty period	18 months	

GV2G254

Sets of Busbars GV2G ••• with Terminal Block GV1G09



Sets of Busbars GV2G245, GV2G254, GV2GR272



	I
GV2G245 (2 x 45 mm)	89
GV2G254 (2 x 54 mm)	98
GV2G272 (2 x 72 mm)	116