



Main

Range of product	C120 C60 DPN I-NA ID
Device short name	OF
IP degree of protection	IP20 conforming to IEC 60947-2
Signal contacts composition	1 NO

Complementary

Mounting mode	Fixed
Wire stripping length	9 mm
Tightening torque	1 N.m
Auxiliary connection terminal	Clamp terminal 1.5 mm ² with cable end cable end Clamp terminal 2 cable(s) ≤ 2.5 mm ² Clamp terminal 1 cable(s) ≤ 2.5 mm ²
[Ie] rated operational current	AC-12: 3 A 380...415 V AC 50/60 Hz AC-12: 6 A 220...240 V AC 50/60 Hz DC-12: 1 A 130 V DC DC-12: 6 A 24 V DC DC-12: 2 A 48 V DC DC-12: 1.5 A 60 V DC
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	1
Depth	73 mm
Height	84 mm
Width	9 mm

Environment

Product certifications	ASEFA ASTA KEMA LCIE
Standards	IEC 60947-2
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C
Pollution degree	3 conforming to IEC 60947-2
Relative humidity	95 % (55 °C)
Tropicalisation	2 conforming to IEC 60947-2
RoHS EUR conformity date	0638
RoHS EUR status	Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.