



Main

Range of product	C60
Device short name	OF
Signal contacts composition	1 NO

Complementary

[Ie] rated operational current	AC-12: 3 A AC 50/60 Hz 277 V AC-12: 6 A AC 50/60 Hz 220...240 V DC-12: 6 A DC 12...24 V DC-12: 2 A DC 48 V DC-12: 1.5 A DC 60 V DC-12: 1 A DC 130 V
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	1
Height	84 mm
Width	9 mm
Depth	73 mm
Auxiliary connection terminal	Pad terminal 1 cable(s) 2.5 mm ² Pad terminal 2 cable(s) 1.5 mm ²
Wire stripping length	9 mm
Tightening torque	1 N.m

Environment

Standards	IEC 60947-5-1
Product certifications	ASEFA ASTA KEMA LCIE
IP degree of protection	IP20 conforming to IEC 60947-2
Pollution degree	3 conforming to IEC 60947-2
Tropicalisation	2 conforming to IEC 60947-5-1
Relative humidity	95 % (55 °C)
RoHS EUR conformity date	0638
RoHS EUR status	Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.