



Main

Range of product	Preventa Safety automation
Product or component type	Preventa safety module
Safety module name	XPSECP
Safety module application	Increasing the number of safety contacts
Safety use category	Category 4 maximum conforming to EN 954-1/ISO 13849-1
Function of module	Increasing the number of safety contacts
Output type	Relay 8 NO, volt-free
[Us] rated supply voltage	24 V AC (- 20...10 %) 24 V DC (- 20...20 %)
Number of additional circuits	1 NC + 1 solid state output
Safety level	Can reach PL e/category 4 conforming to EN 954-1/ISO 13849-1 Can reach SIL 3 conforming to EN/IEC 62061

Complementary

Supply frequency	50/60 Hz
Power consumption	<= 5 VA
Input protection type	Internal, electronic
Breaking capacity	B300: holding 360 VA AC-15 for relay output B300: inrush 3600 VA AC-15 for relay output
Breaking capacity	10 mA/48 V for solid state output circuit 20 mA/24 V for solid state output circuit 1.5 A/24 V - L/R = 50 ms, DC-13 for relay output
Output thermal current	6 A per relay for relay output
[Ith] conventional free air thermal current	< 30 A for relay output
Associated fuse rating	6 A gG for relay output conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200
Minimum output current	10 mA for relay output
Minimum output voltage	17 V for relay output
Response time on input open	<= 20 ms
[Ui] rated insulation voltage	300 V, degree of pollution 2 conforming to IEC 60647-5-1, DIN VDE 0110 part 1
[Uimp] rated impulse withstand voltage	4 kV overvoltage category III, conforming to IEC 60647-5-1, DIN VDE 0110 part 1
Local signalling	3 LEDs
Connections - terminals	Captive screw clamp terminals: 1 x 4 mm ² without cable end Captive screw clamp terminals: 2 x 2.5 mm ² with cable end
Mounting support	35 mm symmetrical DIN rail
Product weight	0.55 kg

Environment

Standards	EN/IEC 60204-1 EN/IEC 60947-5-1
Product certifications	CSA TÜV UL
IP degree of protection	IP20(Terminals) conforming to EN/IEC 60529 IP40(Enclosure) conforming to EN/IEC 60529
Ambient air temperature for operation	-10...55 °C
Ambient air temperature for storage	-25...85 °C