



Main

Range of product	INS630b...2500 INV630b...2500 NG160 NSC100
Device short name	OF SD SDE SDV
Signal contacts composition	1 NO/NC

Complementary

Auxiliary contacts type	Standard
[I _{th}] conventional free air thermal current	6 A
[I _e] rated operational current	AC-12: 6 A AC 50/60 Hz 24 V AC-12: 6 A AC 50/60 Hz 48 V AC-12: 6 A AC 50/60 Hz 110 V AC-12: 6 A AC 50/60 Hz 220/240 V AC-12: 6 A AC 50/60 Hz 380/440 V AC-12: 6 A AC 50/60 Hz 480 V AC-12: 6 A AC 50/60 Hz 660/690 V AC-15: 6 A AC 50/60 Hz 24 V AC-15: 6 A AC 50/60 Hz 48 V AC-15: 5 A AC 50/60 Hz 110 V AC-15: 4 A AC 50/60 Hz 220/240 V AC-15: 2 A AC 50/60 Hz 380/440 V AC-15: 1.5 A AC 50/60 Hz 480 V AC-15: 0.1 A AC 50/60 Hz 660/690 V DC-12: 6 A DC 24 V DC-12: 2.5 A DC 48 V DC-12: 0.6 A DC 110 V DC-12: 0.3 A DC 250 V DC-14: 1 A DC 24 V DC-14: 0.2 A DC 48 V DC-14: 0.05 A DC 110 V DC-14: 0.03 A DC 250 V
Minimum load	100 mA at 24 V

Environment

RoHS EUR conformity date	0701
RoHS EUR status	Compliant