



Main

Range of product	Acti 9
Product or component type	Double OC or fault contact
Device short name	IOF/SD+OF
Signal contacts composition	2 C/O
[In] rated current	1 A: 130 V DC 1.5 A: 60 V DC 2 A: 48 V DC 6 A: 24 V DC 3 A: 415 V AC - 50/60 Hz 6 A: 240 V AC - 50/60 Hz
9 mm pitches	1

Complementary

Range compatibility	Acti 9 iSW-NA Acti 9 iC60 Acti 9 iC65 Acti 9 iC60 RCBO Acti 9 iID Acti 9 ARA Acti 9 RCA Acti 9 iDPN (China version) Acti 9 iDPN Vigii Acti 9 iC40
Local signalling	Mechanical indicator
Mounting mode	Fixed
Mounting support	DIN rail
Height	90 mm
Width	9 mm
Depth	73 mm
Net weight	43 g
Colour	White
Connections - terminals	Screw clamp terminal2 cable(s) 2.5 mm ² - rigid

Screw clamp terminal2 cable(s) 1.5 mm² - flexible with ferrule
Screw clamp terminal1 cable(s) 0.5...2.5 mm² - flexible
Screw clamp terminal1 cable(s) 1...4 mm² - rigid

Wire stripping length	10 mm
Tightening torque	1 N.m

Environment

Standards	EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	Download RoHS China Declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------