



### Main

Range of product	LT3
Device short name	LT3SE
Product or component type	Thermistor protection units
[Uc] control circuit voltage	24...48 V DC
Reset	Manual

### Complementary

Control circuit voltage limits	0.8...1.25 U <sub>c</sub>
Contacts type and composition	1 NC + 1 NO dual voltage
[I <sub>th</sub> ] conventional free air thermal current	5 A for output control relay
[U <sub>i</sub> ] rated insulation voltage	500 V AC output control relay
[U <sub>e</sub> ] rated operational voltage	250 V AC 50/60 Hz for output control relay
Signalling function	Voltage indication Fault indication
Control type	Manual reset Manual test
Probe interchangeability	Label mark A conforming to IEC 60034-11
Hold-in power consumption W	< 1 W
Hold-in power consumption VA	>= 2.5 VA
Resistance	2700...3100 Ohm tripping 1500...1650 Ohm reset
Number of probes	<= 6
Input voltage	< 7.5 V (4000 Ohm) for probe conforming to IEC 60034-11 < 2.5 V (1500 Ohm) for probe
Short circuit detection resistance	< 20 Ohm
Condition of use	Connection of probes 500 m for >= 1.5 mm <sup>2</sup> Connection of probes 1000 m for >= 2.5 mm <sup>2</sup>
[U <sub>imp</sub> ] rated impulse withstand voltage	2.5 kV
Operational power in VA	100 VA at 220 V - electrical durability: 500000 cycles
Breaking capacity	6 A at 120 V AC AC-16 3 A at 250 V AC AC-16 2 A at 24 V DC DC-13
Connections - terminals	Power circuit: cage type connector 2 cable 1...2.5 mm <sup>2</sup> - cable stiffness: solid - without cable end Power circuit: cage type connector 2 cable 1...2.5 mm <sup>2</sup> - cable stiffness: flexible - without cable end Power circuit: cage type connector 2 cable 0.75...2.5 mm <sup>2</sup> - cable stiffness: solid - with cable end Power circuit: cage type connector 2 cable 0.75...2.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end Power circuit: cage type connector 1 cable 1...2.5 mm <sup>2</sup> - cable stiffness: solid - without cable end Power circuit: cage type connector 1 cable 1...2.5 mm <sup>2</sup> - cable stiffness: flexible - without cable end Power circuit: cage type connector 1 cable 0.75...2.5 mm <sup>2</sup> - cable stiffness: solid - with cable end Power circuit: cage type connector 1 cable 0.75...2.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end

Tightening torque	0.8 N.m
Height	100 mm
Width	22.5 mm
Depth	100 mm
Product weight	0.22 kg

## Environment

Standards	IEC 60034-11 VDE 0660
Product certifications	LROS (Lloyds register of shipping)
IP degree of protection	IP20 conforming to VDE 0106 IP20 conforming to IEC 60529
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C conforming to IEC 60068-2-2 -40...85 °C conforming to IEC 60068-2-1
Operating altitude	> 1500...3000 m with derating in temperature <= 1500 m without derating in temperature
Vibration resistance	2.5 gn 2...25 Hz conforming to IEC 60068-2-6 1 gn 25...150 Hz conforming to IEC 60068-2-6
Shock resistance	5 gn 11 ms conforming to IEC 60068-2-27
Electromagnetic compatibility	Susceptibility to electromagnetic fields - test level level 3 conforming to IEC 61000-4-3 Surge resistance 1.2/50-8/20 - test level level 4 conforming to IEC 61000-4-5 Resistance to fast transient - test level level 3 conforming to IEC 61000-4-4 Resistance to electrostatic discharge - test level level 3 conforming to IEC 61000-4-2 Immunity to microbreaks and voltage drops conforming to IEC 61000-4-11

## Contractual warranty

Period	18 months
--------	-----------