



Main

| | |
|---------------------------|---|
| Range | Thalassa |
| Product name | Thalassa PLM |
| Device short name | PLM |
| Device application | Multi-purpose |
| Product or component type | Compact enclosure |
| Enclosure nominal height | 847 mm |
| Enclosure nominal width | 636 mm |
| Enclosure nominal depth | 300 mm |
| Enclosure mounting | Wall mounted |
| Device composition | Lock 2 Door 1 Body 1 |
| Body type | Built-in canopy One piece moulded with notches in the rear |
| Door type | Transparent |
| Lock type | 3 mm double-bar lock |

Complementary

| | |
|-----------------------------|--|
| Number of locks | 2 |
| Mounting plate description | Without mounting plate |
| Accessibility for operation | Front |
| Removable parts | Door by hinges |
| Material | Polyester reinforced with fibreglass body Tempered glass door |
| Colour | Grey RAL 7035 |
| Standards | IEC 62208 NEMA classification 4X NEMA classification 13 |
| Product certifications | UL |

Environment

| | |
|-------------------------------------|------------------|
| IP degree of protection | IP66 IEC 60529 |
| IK degree of protection | IK08 IEC 62262 |
| Fire resistance | 960 °C IEC 62208 |
| Ambient air temperature for storage | -35...90 °C |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1511 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |